



US008608981B2

(12) **United States Patent**  
**Elliott et al.**

(10) **Patent No.:** **US 8,608,981 B2**  
(45) **Date of Patent:** **Dec. 17, 2013**

(54) **METHODS FOR SULFATE REMOVAL IN LIQUID-PHASE CATALYTIC HYDROTHERMAL GASIFICATION OF BIOMASS**

(75) Inventors: **Douglas C. Elliott**, Richland, WA (US);  
**James Oyler**, Salt Lake City, UT (US)

(73) Assignees: **Battelle Memorial Institute**, Richland, WA (US); **Genifuel Corporation**, Salt Lake City, UT (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 10 days.

(21) Appl. No.: **13/541,003**

(22) Filed: **Jul. 3, 2012**

(65) **Prior Publication Data**

US 2012/0280180 A1 Nov. 8, 2012

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 12/339,876, filed on Dec. 19, 2008, now Pat. No. 8,241,605.

(60) Provisional application No. 61/024,970, filed on Jan. 31, 2008.

(51) **Int. Cl.**  
**C01B 3/38** (2006.01)  
**C01B 3/24** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **252/373; 423/650**

(58) **Field of Classification Search**

USPC ..... 252/373  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2006/0265954 A1\* 11/2006 Dogru et al. .... 48/197 R  
2007/0000177 A1 1/2007 Hippo et al.  
2009/0126274 A1\* 5/2009 Vogel et al. .... 48/127.7

\* cited by examiner

*Primary Examiner* — Melvin C Mayes

*Assistant Examiner* — Kenneth Vaden

(74) *Attorney, Agent, or Firm* — Klarquist Sparkman, LLP

(57) **ABSTRACT**

Processing of wet biomass feedstock by liquid-phase catalytic hydrothermal gasification must address catalyst fouling and poisoning. One solution can involve heating the wet biomass with a heating unit to a pre-treatment temperature sufficient for organic constituents in the feedstock to decompose, for precipitates of inorganic wastes to form, for preheating the wet feedstock in preparation for subsequent removal of soluble sulfate contaminants, or combinations thereof. Processing further includes reacting the soluble sulfate contaminants with cations present in the feedstock material to yield a sulfate-containing precipitate and separating the inorganic precipitates and/or the sulfate-containing precipitates out of the wet feedstock. Having removed much of the inorganic wastes and the sulfate contaminants that can cause poisoning and fouling, the wet biomass feedstock can be exposed to the heterogeneous catalyst for gasification.

**20 Claims, 2 Drawing Sheets**

